

500 Watt 90° *HYBR-LINE* Coupler



1000-2000 MHz



Model: HBL-1000-2000-R5H1




| | |
|---------------------------|------------------------------|
| Frequency: | 1000 - 2000 MHz |
| Amplitude Balance: | ±0.50 dB Max. |
| Power: | 500 Watts CW |
| Phase Balance: | ± 3° Typical |
| Insertion Loss: | 0.25 dB Max. |
| Isolation: | 20 dB Min. |
| VSWR: | 1.25:1 Max. All Ports |

HBL Series Drop-In Hybrid couplers provide High Power dividing or combining while exhibiting excellent phase and amplitude balance over continuous broadband operation. Solid compact designs are able to operate in a wide variety of environments, which include Medical, Industrial, Commercial wireless, Military, and Space. The **P3** library of designs allows for modifications of standard designs to be made quickly and inexpensively to meet specific requirements with short delivery times. Consult factory for special requirements or frequency ranges.

NOTES:

Material: Aluminum Alloy. 6061-T651
 Finish: Chem-Film, Clear Iridite MIL-DTL-5541F
 Operating Temperature: -55°C to +85°C



www.preferredpowerproducts.com

Tel: 1-772-291-2549 | sales@preferredpowerproducts.net

STUART, FL 34997