

250 Watt 90° **HYBR-LINE** Coupler Sheet



88-108 MHz

Model: HBL-88-108-R25B2



Frequency:	88 - 108 MHz
Amplitude Balance:	±0.50 dB Max.
Power:	250 Watts CW
Phase Balance:	± 1.5° Typical
Insertion Loss:	0.25 dB Max.
Isolation:	23 dB Min.
VSWR:	1.15:1 Max. All Ports

HBL Series Drop-In Hybrid couplers provide High Power dividing or combining while exhibiting excellent phase and amplitude balance over continuous broad-band operation. Solid compact designs are able to operate in a wide variety of environments, which include Medical, Industrial, Commercial wireless, Military, and Space. The **P3** library of designs allows for modifications of standard designs to be made quickly and inexpensively to meet specific requirements with short delivery times. Please consult factory for special requirements or frequency ranges.

NOTES:

Material: Aluminum Alloy. 6061-T651
 Finish: Chem-Film, Clear Iridite MIL-DTL-5541F
 Operating Temperature: -55°C to +85°C

Specifications subject to change without notice

NOTES:

- TOLERANCE IS ±.020, (UNLESS OTHERWISE SPECIFIED)
- LEAD WIDTH: .120" TYP.
- LEAD LENGTH: .150" TYP.
- LEAD MATERIAL: 99.99% PURE SILVER (.005" THK.)

INPUT	OUTPUT			
	A	B	C	D
A	----	Termination	0°	-90
B	Termination	----	-90	0°
C	0°	-90	----	Termination
D	-90	0°	Termination	----

www.preferredpowerproducts.com

Tel: 1-772-291-2549 | sales@preferredpowerproducts.net

STUART, FL 34997